

A B
A B
A B
A B

TN Chiller  
 TB Freezer  
 TB/TN Dual Temp  
 TC Heated  
 TC/TN Hot&Cold  
 N Non-refrigerated  
 RS - Static  
 RV - Ventilated  
 RS/TC S - Static and Dry Heat convertible  
 RV/TC S - Ventilated / Dry Heat convertible  
 HUR - Meat  
 CH - Chocolate  
 TC S - Dry Heat  
 TC BM - Bainmarie  
 N - Non-refrigerated

<b>H</b> 2000	2000	2000	2000
<b>D</b> 900	900	900	900
<b>L</b> 937	1250	1875	2500

**3M1** sandwiches • dairy • drinks • delicatessen • fresh products

**Installation**  
• Plug in

**Configuration**  
5 adjustable shelves  
Depth 450mm  
**Temperature range**  
-1/+5°C

**Refrigerant**  
R290

**Refrigeration**  
Ventilated

**Compressor**  
Hermetic

**Climate & product class**  
3M1

**Side panels**  
25mm

**Closing system**  
Swing doors (tempered double glass  
4+10+4mm)

**Lighting**  
Optional (canopy and shelves)

**Equipment handling**  
Adjustable feet

**Defrost**  
Air



External dimensions (LxDxH)	Sides 25mm thick	Adjustable feet Swivel casters	987x900x2000mm	1300x900x2000mm	1925x900x2000mm	2550x900x2000mm
		Adjustable feet Swivel casters				
<b>Net volume</b>			465,50 dm3	621,00 dm3	931,50 dm3	1242,00 dm3
<b>Weight (net)</b>			173 kg	231 kg	347 kg	463 kg
<b>Refrigeration</b>	Ventilated					
<b>Refrigerant</b>	R290					
<b>Climate class</b>	3					
<b>Operating conditions</b>	25 °C / 60 %RH					
<b>Product temperature</b>	-1/+5°C					
<b>Compressor (q.ty-type)</b>	1 Hermetic	1 Hermetic	1 Hermetic	1 Hermetic	1 Hermetic	1 Hermetic
<b>Defrost</b>	Air					
<b>Power supply</b>	230 V / 1 Ph / 50 Hz					
<b>Electrical input (nominal)</b>	584 W/ 2.86 A	601 W/ 2.94 A	649 W/ 3.18 A	783 W/ 3.84 A		
<b>Electrical input (defrost)</b>	0 W/ 0 A	0 W/ 0 A	0 W/ 0 A	0 W/ 0 A		

Technical sheet about models with condensing unit included with air / el. heater

**Setup**

Shelves dimensions (LxD)	930x450mm	1240x450mm	2pcx930x450mm	2pcx1240x450mm
	930x450mm	1240x450mm	2pcx930x450mm	2pcx1240x450mm
	930x450mm	1240x450mm	2pcx930x450mm	2pcx1240x450mm
	930x450mm	1240x450mm	2pcx930x450mm	2pcx1240x450mm
	930x450mm	1240x450mm	2pcx930x450mm	2pcx1240x450mm

Height	Length	Model type	Total display area (m2)	Temperature class	Recommended temperature (°C)	Energy class	Energy efficiency index EeI	Annual energy consumption kWh/A	Light source type and class
2000	937mm	Vertical	1,51	M1	+1°C	B	18,17	1918,80	/
	1250mm	Vertical	2,02	M1	+1°C	B	15,55	1972,64	/
	1875mm	Vertical	3,03	M1	+1°C	B	12,60	2132,79	/
	2500mm	Vertical	4,04	M1	+1°C	B	12,15	2572,16	/

Configuration: Vertical refrigerated show case plug in, closed with swing doors with five shelves defrosting-air

