

CROSS-SECTION	INFORMATION
	<p>type: SWING DOORS code: temp. class: 3L1 working temp.: -15 / -18 °C power supply: 230V/50Hz refrig. supply: PLUG-IN refrigerant: R290 defrosting: electrical fans: electrical lighting: vertical no of rows: 3 single kind of lighting: LED doors: themopane glass type: hinged opened: left + right</p>

EXPOSITION SURFACES							
surface	*	rows number	product	width [mm]	load height [mm]	angle [°]	load [kg/m ²]
hanged shelve	1	4	normal	500	200	0	35
bottom shelve	2	1	normal	565	210	0	55

CHARACTERISTIC			
module	*	[-]	2343
module length	3	[mm]	2343
module height	4	[mm]	2000
module width	5	[mm]	900
display height	6	[mm]	1620
display opening area	7	[m ²]	3.80
total display area (TDA)	8	[m ²]	3.80
visibility of products (VPA)	9	[m ²]	1.80
net volume	10	[dm ³]	1215.20
refrigerated shelf area	11	[m ²]	6.01
net weight	12	[kg]	469

NOTICE
* development version
The information included in the Technical Data of device refers to certain equipment defined in the first page. All values and parameters are defined on the basis of standard PN EN ISO 23953 for the given temperature class, range of temperature and equipment

RECOMMENDATIONS
The correct work of devices enables its non-failure work with energetical rated parameters
Complying with the rules of device loading guarantees the stable temperature parameters of stored products Properly selected operating parameters allow you to greatly reduce the cost of electricity consumption.
THE MANUFACTURER RESERVES THE RIGHT TO ALTER THE FEATURES AND TECHNICAL SPECIFICATIONS OF ITS PRODUCTS.

AMBIENT PARAMETERS			
1	climate class	-	3
2	max. ambient temperature	[°C]	25
3	max. ambient humidity	[%]	60
4	illumination	[lux]	200
5	max. ambient air speed	[m/s]	0.2

DEVICE WORKING PARAMETERS			
6	device temperature class	-	L1
7	cabinet temperature	[°C]	-15 / -18
8	refr. evaporating / condensing temp.	[°C]	-30/+45
9	suction superheat	[K]	5
10	refrigerant	R290	

COOLING DATA			
module	*	[-]	2343
unit cooling capacity	11	[W]	1530
inlet tube	13	[mm]	10
outlet tube	14	[mm]	12
refrigerant fluid	15	[kg]	0.30

ELECTRICAL DATA			
module	*	[-]	2343
power supply	16	[V/Hz]	230/50
compressor	17	[W]	1672
	18	[A]	8.19
defrosting, hot gas	19	[W]	2512
	20	[A]	12.31
fans	21	[W]	240
	22	[A]	1.18
lighting	23	[W]	65
	24	[A]	0.32
heaters	25	[W]	194
	26	[A]	0.95

RATED DATA			
module	*	[-]	2343
power rate, current	27	[W]	2938
	28	[A]	14.40

ELECTRICAL CONSUMPTION			
module	*	[-]	2343
TEC	29	[kWh/24h]	32.32
AE	30	[kWh/a]	11795.67
EEL	31		36.38
			Energy Class: D

WORKING PARAMETERS							
32	defrosting time	[h/24h]	2	34	working time of heaters	[h/24h]	12
33	working time of fans	[h/24h]	12	35	working time of lighting	[h/24h]	12

PARAMETERS OF ELECTRICAL TERMINALS						
36	power supply P+N+PE	[V/Hz]	230/50	37	electrical connection - plug-in socket	230V/16A

TEC - TOTAL ENERGY CONSUMPTION EEL - ENERGY EFFICIENCY

NOTICE

In the devices with night curtain or covers, the covering time is 12h.

CONTROLLING PARAMETERS							
1	set point ST	[°C]	-20	6	correction ST by night	[°C]	-
2	differential ST	[°C]	2	7	defrosting number	[il/24]	2
3	set point correction ST	[°C]	-	8	temperature of defrosting end	[°C]	12
4	fan running during defrosting	[yes/no]	yes	9	maximum time of defrosting	[min]	45
5	stop fans temperature	[°C]	-	10	dripping time	[min]	0

1 - LOCALIZATION OF CONTROL PROBE

2 - LOCALIZATION OF DEFROSTING PROBE, DEFROSTING HEATERS

lm - MODULE LENGTH

S1 - CONTROL PROBE

S2 - DEFROSTING PROBE

le- LENGTH OF EVAPORATOR

Hd - DEFROSTING HEATER

EV - EXPANSION VALVE

AD - AIR FLOW DIRECTION

Notice

Automatic control system should ensure deicing from evaporator and removal of water.

The devices in line must be controlled dependently. The control system of particular devices in line must synchronize the start and end of defrosting process




The defrosting process should be managed by temperature. 9-th parameter should be treated as emergency.

If the parameter number 4 is set on "no" value, the fans work depends on temperature value of defrosting probe (parameter no 5). During the dripping time of evaporator the fans don't work.

The correction set point by night ensures the correct device work with closed curtains. The parameter beneficially influences energy savings.

If it is necessary, please modify parameters to provide good work of device.



 REFRIGERATION CONNECTION UNDER DEVICE UPPER REFRIGERATION CONNECTION	 ELECTRIC CONNECTION UNDER DEVICE UPPER ELECTRICAL CONNECTION	 CONDENSAT WATER DRAINAGE
<p>NOTICE To arrange a device you need to ensure its correct ventilation. The surfaces of side glass must be moved from walls in order to guarantee air flow to dry them. To ensure the correct work the refrigeration devices must be moved from a wall on the distance of 50mm (remote device) and 100mm (plug-in). THE MANUFACTURER RESERVES THE RIGHT TO ALTER THE FEATURES AND TECHNICAL SPECIFICATIONS OF ITS PRODUCTS.</p>		