

Fiche technique / Technisches Datenblatt / Technical data sheet /
Scheda tecnica / Ficha técnica



AN170M-1D-R2

	Form	kW	T° Out	T° In -15°C		T° In -20°C		T° In -25°C		V			kg
				W/f	m3/Vol	W/f	m3/Vol	W/f	m3/Vol			m3/pack	
052-151	AN120M-1C-R2												
	1	0,65	25°C	872	10,9	744	7,1	628	4,6	230/1N	50 Hz	65	0,38
			32°C	815	7,5	694	4,9	583	3,3				
			43°C	723	4,1	612	2,8	510	1,8				
	AN170M-1D-R2												
	1	0,91	25°C	1160	18,6	987	10,5	828	6,8	230/1N	50 Hz	72	0,38
			32°C	1090	11,3	925	7,5	776	4,9				
			43°C	966	6,3	817	4,2	679	2,8				
	AN203T-2F-R2												
	2	1,3	25°C	1988	41,7	1684	25,7	1411	15,5	400/3N	50 Hz*	116	0,82
			32°C	1870	29,4	1579	18,2	1316	10,3				
			43°C	1660	14,9	1398	9,1	1158	6,1				
	AN300T-3G-R2												
	3	1,8	25°C	2720	64,9	2313	40,8	1939	25,7	400/3N	50 Hz*	143	1,17
			32°C	2549	46,8	2165	29,6	1812	18,6				
			43°C	2248	25,8	1899	15,8	1579	9,3				
	AN400T-3H-R2												
	3	2,1	25°C	2992	73,9	2566	47,3	2175	30,4	400/3N	50 Hz*	156,6	1,17
			32°C	2793	53,5	2392	34,4	2023	22				
			43°C	2468	29,9	2108	19,3	1774	11				

