
Climate class		: 4(CC2 to EN22044)
Temperature range	(°C)	: +1 / +9°C
Power	(W)	: 730W / 4,3A
Voltage/freq.	(V / Hz.)	: 220-240v / 50HZ

TECHNICAL SPECIFICATIONS

External dimensions	(WXDXH)mm	: 1200x760x2078
Internal dimensions	(WXDXH)mm	: 1125x622x1571
Package dimensions	(WXDXH)mm	: 1230x770x2139
Gross volume	(L)	: 1142
Net volume	(L)	: 1088
Gross weight	(kg)	: 199
Net weight	(kg)	: 185
Outer body		: 0.6 mm CRS
Inner liner		: 0.45 mm PRE-PAINTED
Insulation material		: Rigid P.U.
Insulation density		: 38~40 kg/m³
Internal light		: Yes 2 x Vertical Led
Canopy light		: No
Light Switch		: Yes
Door Switch		: Yes
Levelling leg (front)		: Yes
Levelling leg (back)		: No
Roller		: 4 Castor
Comp. capacity		: CUBIGEL, 2065 W
Evaporator		: FIN CU
Evap. ventilator		: 2 x 5/33W Non Ec Axial Fan - SAIWEI
Condenser		: WOT
Cond. ventilator		: 7/38W Non Ec Axial Fan - SAIWEI
Thermostat		: MECHANIC
Refrigerant		: R290
Refrigerant charge	(g)	: 122 grams
Approvals		: CE,ROHS

* External depth is without back stopper.

