

Climate class		: CC2 (EN 22044)
Temperature range	(°C)	: +1 / +9 C
Power	(W)	: 880 W - 4,5A
Voltage/freq.	(V / Hz.)	: 220-240V/50Hz

TECHNICAL SPECIFICATIONS

External dimensions	(WXDXH)mm	: 1600 X 736 X 2050
Internal dimensions	(WXDXH)mm	: 1500 X 623 X 1545
Package dimensions	(WXDXH)mm	: 1641X 777 X 2180
Gross volume	(L)	: 1455
Net volume	(L)	: 1326
Gross weight	(kg)	: 273
Net weight	(kg)	: 247
Outer body		: 0.6 mm.DKP / sheet steel
Inner liner		: 0.45 mm. Boyalı Sac / Prepainted Sheet
Insulation material		: Sert P.U. / Rigid P.U.
Insulation density		: 38~40 kg/m³
Internal light		: Yes 6 x Vertical
Canopy light		: No
Light Switch		: Yes on the thermostat
Door Switch		: Yes
Levelling leg (front)		: 2 Adet / 2 Pcs.
Levelling leg (back)		: -
Roller		: 6 Adet / 6 Pcs.
Comp. capacity		: Cubigel, 584 W
Evaporator		: Fin Evap
Evap. ventilator		: AXIAL 7/31W NON-EC&PROPELLER Ø200/34°(2
Condenser		: WOT
Cond. ventilator		: AXIAL 18/75W NON_EC&PROPELLER Ø250/34°
Thermostat		: ELECTRONIC
Refrigerant		: R290
Refrigerant charge	(g)	: 150
Approvals		: CE

* External depth is without back stopper.

