



► Working conditions

- Location: **Indoor**

	Min	Max
Ambient temperature	+10° C / +50° F	+43° C / 110° F
Water temperature	+3° C / +37° F	+32° C / +90° F
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

► Performances

		Water temperature					
		7° C	45° F	15° C	60° F	21° C	70° F
Air temperature	10° C	23 kg					
	50° F		51 lbs				
	21° C			21 kg			
	70° F				46 lbs		
	32° C					16 kg	
	90° F						35 lbs

► Connections

All measures are referred to the rear bottom-left corner (L-H-Ø)

- ① Water in.: 88 mm / 3 7/16" - 184 mm / 7 4/16" - 3/4" ② Water out.: 45 mm / 1 12/16" - 138 mm / 5 7/16" - 24 mm / 15/16"
- ③ Electrical connections: 41 mm / 1 10/16" - 73 mm / 2 14/16"

► Technical information

Production in 24h	21 kg / 46 lbs
Store capacity, up to	4 kg / 9 lbs
Cooling system	A - W
Kind of cube	D-13g
Refrigerant	R290
Standard voltage	220-240 V ~ 50 Hz
Average power consumption	260 W
Fuse	10 A
Electrical consumption	35 kWh/100kg

Water consumption	A: 4 l/kg - 48 gal/100 lbs
	W: 25 l/kg - 300 gal/100 lbs
Sizes (L-P-H mm)	355 - 404 - 590
(L-P-H in)	14 - 15 14/16 - 23 4/16
Sizes with pack (L-P-H mm)	415 - 445 - 780
(L-P-H in)	16 5/16 - 17 8/16 - 30 11/16
Net weight	27,5 kg / 61 lbs
Gross weight	34 kg / 75 lbs
Finish	AISI 304 stainless steel, scotch brite - ABS blue or grey

All the technical information must be considered at the following conditions:

Sizes without feet

Standard Cube (13 g)

Ambient temperature +21° C

Water temperature +15° C

Electrical consumption at +32° C (standard voltage)

Average power consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice