

CHARACTERISTICS

Climate class		: 4
Temperature range	(°C)	: -24 / -18
Power	(W)	: 4 A / 670 W
Voltage/freq.	(V / Hz.)	: 220-240V/50Hz

TECHNICAL SPECIFICATIONS

External dimensions	(WXDXH)mm	: 640 X 670 X 1875
Internal dimensions	(WXDXH)mm	: 490 X 469 X 1570
Package dimensions	(WXDXH)mm	: 650 X 705 X 1975
Gross volume	(L)	: 382
Net volume	(L)	: 361
Gross weight	(kg)	: 96
Net weight	(kg)	: 89
Outer body		: 0.5 mm.DKP / sheet steel
Inner liner		: 0.5 mm. Boyalı Sac / Prepainted Sheet
Insulation material		: Sert P.U. / Rigid P.U.
Insulation density		: 38~40 kg/m ³
Internal light		: 1 Pcs Horizontal
Canopy light		: No
Light Switch		: No
Door Switch		: Yes
Levelling leg (front)		: 2 Adet / 2 Pcs.
Levelling leg (back)		: -
Roller		: 2 Adet / 2 Pcs.
Comp. capacity		: CUBIGEL 651W
Evaporator		: WOT Evap
Evap. ventilator		: 24 Watt Radial
Condenser		: Back Condenser
Cond. ventilator		: 24 Watt Radial
Thermostat		: Mechanical
Refrigerant		: R290
Refrigerant charge	(g)	: 110
Approvals		: CE

* External depth is without back stopper.

